

Declaration of Performance**No. K-BS2013-2020****Next Door Systems BV**

- | | | |
|----------|--|--|
| 1 | <i>Unique identification code of the product type:</i> | Fire screen FS2 |
| 2 | <i>Type, batch or serial number or any other element for the identification of the product</i> | Order, position and serial number, (label at door) |
| 3 | <i>Intended use of the construction</i> | Industrial fire rated operable textile curtain |
| 4 | <i>Name and address of manufacturer</i> | Next Door Systems BV
Randweg 19
8304 AS Emmeloord (NL) |
| 5 | <i>Name of representative</i> | Jaap Aardema |
| 6 | <i>System of assessment and verification of constancy of performance of the construction product as set out in annex V</i> | System 1 + System 3 |
| 7 | <i>In case of the Declaration of Performance concerning a construction product covered by a harmonized standard EN 16034 The notified product verification body Efectis France NB n° 1812 has performed in system 1 the determination of the product type on base of type test (including sampling), initial inspection of the manufacturing company and in-house production control plus monitoring, appraisal and evaluation of the in-house production control and issued the certificate of constancy of the product performance (certificate n° 1812-CPR-1683)</i> | |

8 Declared performance

Essential characteristics	Performance	Harmonized Standard
<i>Water tightness</i>	NPD	EN 13241:2003 + A2:2016
<i>Release of dangerous substances</i>	NPD	
<i>Resistance to wind load</i>	Class 0	
<i>Thermal resistance</i>	NPD	
<i>Air permeability</i>	NPD	
<i>Safe opening (for vertically moving doors)</i>	NPD	
<i>Definition of geometry of glass components</i>	NPD	
<i>Mechanical resistance and stability</i>	Pass	
<i>Operating forces (for power operated doors)</i>	NPD	
<i>Durability of water tightness, thermal resistance and air permeability against degradation</i>	NPD	
<i>Resistance to fire</i>	EW 60 max 10.000x8.000 mm	EN 16034:2014
<i>Smoke control</i>	NPD	
<i>Ability to release</i>	Released	
<i>Self-closing</i>	C	
<i>Durability of ability to release</i>	NPD	
<i>Durability of self-closing; - against degradation - against ageing</i>	NPD NPD	

- 9** The performance of the product according to 1 and 2 corresponds to declared performance according to 8. The manufacturer according to 4 alone is responsible for the creation of this declared performance.

Signed for the manufacturer and on behalf of the manufacturer by

Jaap Aardema, Director



Emmeloord, 05-03-2020